



VD

41.0200.26.2
81.2913.00.2
80.2190.00.2 □

MF

80.1428.00.2
41.0208.19.2
41.0201.26.2
81.2970.00.2
80.2235.00.2 ◇

VP

80.1428.00.2
41.0207.19.2
80.6580.00.2
41.0202.26.2
81.2912.00.2
80.2189.70.2 ◇

VC (only 1540.1)

80.1428.00.2
80.2235.00.2 ◇
81.2970.00.2
41.0208.19.2
32.0098.07.2
86.3001.00.2 (x8)
41.0210.26.2 [22Nm-16.2Lbft]

OPTIONAL FRONT

36.9814.97.3

31.1466.32.2
84.3560.00.2(x3)
84.1846.00.2(x3)

REAR

31.1482.32.2

86.1846.00.2 (x4)
84.3560.00.2(x4)

SAFETY VALVE

24.3050.97.3

MATERIALE - MATERIAL	KIT MEMBRANE - DIAPHRAGMS KIT						KIT VALVOLE - VALVES KIT			KIT POMPA - PUMP KIT	
	BUNA-N	DURAMAX	DESMOPAN	HPS	VITON	/			VD	MF-VP-VC	
STD. - OPT.	STD.	OPT.	OPT.	OPT.	OPT.	STD.					
CODICE - CODE	41.9875.97.3	41.9876.97.3DS	41.9876.97.3	41.9878.97.3	41.9877.97.3	41.9870.97.3			41.9882.97.A	41.9884.97.A	
COMPONENTI COMPONENTS	■	▲	●	▼	■	○			□	◇	

INFORMAZIONI UTILI - USEFUL INFORMATION				
OLIO - OIL	OLIO MOTORE O SEMIIDRAULICO SAE 30 MOTOR OIL OR SEMI-HYDRAULIC OIL			
PRESSIONE DI LAVORO OPERATING PRESSURE	2 ÷ 5	5÷10	10 ÷ 20	20 ÷ 50
ACCUMULATORE	2	2 ÷ 5	5 ÷ 7	6 ÷ 8